

INFLATION GUIDE

Product	Max. Circumference		Product	Max. Circumference	
A-0	28.5 in.	72,0 cm	LD-2	37.7 in.	96,0 cm
A-1	36.0 in.	91,0 cm	LD-3	45.0 in.	114,0 cm
A-2	48.5 in.	123,0 cm	CC-1	34.5 in.	88,0 cm
A-3	58.5 in.	148,0 cm	CC-2	44.5 in.	113,0 cm
A-4	68.0 in.	172,0 cm	CC-3	58.5 in.	148,0 cm
A-5	86.5 in.	220,0 cm	CC-4	68.0 in.	173,0 cm
A-6	106.5 in.	270,0 cm	CC-5	86.5 in.	220,0 cm
A-7	130.0 in.	330,0 cm	CC-6	106.5 in.	270,0 cm
F-1	18.5 in.	47,0 cm	CM-2	44.5 in.	113,0 cm
F-02	25.0 in.	63,8 cm	CM-3	58.5 in.	148,0 cm
F-2	27.0 in.	69,0 cm	G-3	17.3 in.	43,9 cm
F-3	27.0 in.	69,0 cm	G-4	20.4 in.	51,8 cm
F-4	27.0 in.	69,0 cm	G-5	26.7 in.	67,8 cm
F-5	37.0 in.	94,0 cm	G-6	33.0 in.	83,8 cm
F-6	37.0 in.	94,0 cm	HTM-1	18.8 in.	47,8 cm
F-7	47.0 in.	119,0 cm	HTM-2	25.1 in.	63,8 cm
F-8	47.0 in.	119,0 cm	HTM-3	31.4 in.	79,8 cm
F-10	58.0 in.	147,0 cm	HTM-4	38.0 in.	96,5 cm
F-11	74.0 in.	188,0 cm			
F-13	99.0 in.	251,0 cm			

Note: when inflating with an air compressor, set the PSI to 2 lbs. pressure at 20°C

An over-inflated F Series fender has bowed-out sides and a rounded top as shown below.

